

## **TECTYL 437**

### **MSDS Number**

BDTLN

### **National Stock Number**

8030-00-285-1570

### **Product Name**

TECTYL 437

### **Manufacturer**

ASHLAND OIL INC

### **Product Identification**

Product ID:TECTYL 437  
MSDS Date:01/01/1985  
FSC:8030  
NIIN:00-285-1570  
MSDS Number: BDTLN

### **Responsible Party**

ASHLAND OIL INC.  
Emergency Phone: 614-889-3333  
Cage: 81355

### **Contractor**

ASHLAND OIL INC ASHLAND CHEMICAL CO DIV  
2219  
KENT, WA 98031  
US  
800-622-6846  
Cage: 60016

### **Ingredients**

2000 PALE OIL \*5 MG/CUM FOR OIL MIST  
Fraction By Weight: >60%  
ACGIH TLV: 5 MG/CUM\*

### **Hazards**

Effects of Overexposure:EYES-CAN CAUS SEVER IRRTN,REDNES,TEARING,  
BLURRED VISN.SKIN PRLNG CONTCT CAN CAUS MODERAT IRRITATION

### **First Aid**

First Aid:SKN:THOROUGHLY WASH EXPOS AREA W/SOAP & WATR.REMOV CONTAM  
CLOTHNG.LAUNDRER CONTAM CLOTHNG BEFOR REUSE.EYES-FLUSH W/LG AMTS OF  
WATR,LIFTNG UPPR AND LOWER LIDS OCASIONALY.SWALLOWD-GIVE 2 GLASS OF  
WATR;I NDUCE VOMITING IMMED.CALL DR.NEVR GV ANYTHG BY(SUP

### **Fire Fighting**

Flash Point:460F 238C  
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE.  
Fire Fighting Procedures:WATR OR FOAM MAY CAUS FROTHNG WHICH CAN BE  
VIOLENT & (SUPPLY

### **Accidental Release**

Spill Release Procedures:SM SPILL-ABSORB LIQUID ON PAPER,  
VERMICULITE,FLOOR ABSORBENT, OR OTHR ABSORBENT MATRL & TRANSFR TO

HOOD.LG SPIL:PER SONS NT WEARING PROTECEQPMT SHLD BE EXCLUDED FR  
AREA OF SPIL UNTIL CLEAUP HAS BEEN C OMPLETD.STP SPIL AT SOURC;DIKE  
AREA OF SPIL TO PRV

## Handling

Handling and Storage Precautions:CONTNRS OF THIS MATRL MAY BE HAZARDOUS  
WHN EMPTIED.SINCE EMPTIES CONTNRS RETN PRODCT  
RESIDUE(VAP,LIQD,AND/OR SOLID),ALL HAZ PRECAUTIONS GVN.

## Exposure Controls

Respiratory Protection:IF TLV OF ANY COMPNT EXCEEDED, NIOSA/MESA INTLY  
APPRVD SELF-CONT BRE  
Ventilation:LOC.EXHAUST-PROVID SUFFICIENT MECHLGEND AND/OR LOC. EXHAUST.  
Protective Gloves:BUNA-N,NEOPRENE  
Eye Protection:WEAR SAFETY GLASS IN COMP  
Other Protective Equipment:TO PREVNT REPEATD OR PRLNG SKN CONTCT,WR  
IMPERV CLOTHNG/BOOT  
Supplemental Safety and Health  
SPEC FIRE FIGHT:& POSS ENDANGR LIFE OF FIREFIGHTR.SELF-CNTND BREATHING  
APPARAT.W/FACPIECE OPER IN PRESR-DEMD OR OTHR POSITIV PRESSR MODE.  
EMERGENCY: MOUTH TO AN UNCONSCIOUS PERSON.

## Chemical Properties

HCC:N1  
Spec Gravity: < WATE  
Evaporation Rate & Reference:SLOWER THAN ETHER.

## Stability

Stability Indicator/Materials to Avoid:YES  
AVOID CONTCT W/STRONG OXIDIZING AGENTS.  
Hazardous Decomposition Products:MAY FORM TOXIC WATER-CO,CO\*2,VAR  
HYDROCARBNS,SULFUR COMPS E

## Disposal

Waste Disposal Methods:SM SPILL-ALLOW VOLATILE PORTN TO EVAPORAT IN  
HOOD.ALLOW SUFFICIENT TIME F/VAPORS TO COMPLETELY CLEAR HOOD DUCT  
WORK.DESTROY REMAINING BY BURNING IN AN IRON PAN.LG SPIL-DESTROY BY  
LIQUID INCINERATION W /OFF-GAS SCRUBBER.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.